



HITAVEITA
SUÐURNESJA



Technical Challenges of Geothermal Energy Utilisation

Geir Þórólfsson

Mechanical Engineer

HS Orka

Jónas Matthíasson

Mechanical Engineer

Verkís



HITAVEITA
SUÐURNESJA




Hitaveita Suðurnesja Geothermal Power Plants

- Svartsengi 1: 2 x 1 MWe og 50 MJ/s (decommissioned)
 - Svartsengi 2: 75 MJ/s
 - Svartsengi 3: 1 x 6 MWe
 - Svartsengi 4 7 x 1,2 MWe
 - Svartsengi 5: 1 x 30 MWe og 75 MJ/s
 - Svartsengi 6: 1 x 30 MWe
 - Reykjanes : 2 x 50 MWe
- » Total: 324,4 MWe and MJ/s



★ High-temperature system

1226 Year of historic lava flow





Geothermal Power Plant Main Parts

- Geothermal wells
- Well piping
- Separator station
- Steam piping
- Power station
- Steam turbine – Generator
- Cooling system
- Substation, switchyard
- High voltage line



HITAVEITA
SUBURNEZIA



Design tasks

- Mechanical (in approximate time sequence)
 - Preliminary Design: Concept design, dialogs between owner, designers and main machine producer
 - Process Flow diagram (PFD): Showing main equipment, connecting pipelines, valves, and flowrates
 - Process Instrument Diagram (PID): Similar to PID but with all instruments and their codes for function



HITAVEITA
SUBURNEZIA



Design tasks

- Mechanical, continued
 - Piping: Pipe dimensions, Pressure ratings, Design codes and standards, Safety , Pressure drop criteria and calculations
 - Power station Layout
 - Equipment submitted for tendering
 - Detail design



HITAVEITA
SUBURNEZIA



Design tasks

- Electrical equipment
 - High Voltage
 - Single line diagram
 - Transformer specifications
 - Breakers specifications
 - Protection system specifications
 - Low voltage
 - Distribution cubicles
 - Cabling




HITAVEITA
SUBURNEZIA



Design tasks

- Control system
 - Control loops
 - Control equipment
 - Regulators
 - PLC computers
 - Remote monitoring
 - SCADA system
- Civil engineering
- Architectural drawings
- Landscape design

Design of a well





HITAVEITA
SUBURNEZIA



Geothermal wells

Problems in operation

- Scaling
- Corrosion
- Casing collapse
- Liner break
- Leaks
- Gas







HITAVEITA
SUBURNEZIA




Two Phase Pipelines

- Avoid slug flow
 - Incline two phase pipes down
 - Calculate the dimension of condensate pipe lines to ensure there is space for flash steam
- Keep them anchored





HITAVEITA
SUBURNESIA







HITAVEITA
SUBURNEZIA



Rankine Cycle



Svartsengi – Single Line Diagram





HITAVEITA
SUBURNEZIA



Equipment design choices

- Separators: Vertical Cyclone or horizontal gravity?
- Separators on each wellpad or two phase flow pipeline to a central separator station?
- Length of main steam pipe?
- Impulse or reaction steam turbine?
- Cooling tower or natural cooling-water?
- Vacuum pumps: Steam ejectors, water ring pumps, or hybrid?



Reykjanes Plant
separator



HITAVEITA
SUBURNEZIA



Reykjanes Principles

- High separator and inlet pressure to reduce scaling in separators
 - Steam wetness in low pressure stages is high, danger of erosion
- Double flow reaction turbines
 - Lower steam velocity reduces danger of erosion
- Seawater cooled condenser
 - Minimum steam and vapour plumes
- Remote monitoring and control
 - Lowers operation cost
- **Environmentally benign power plant**



HITAVEITA
SUBURNESIA




Design Principles for Reykjanes


- Independent system for each unit, one separator, one moisture separator, one cooling system.
- Easy maintenance
- Ample maintenance space in power station
- Remote operation
- Quality steam




Reykjanes 2 x 50 MW Geothermal Flash Steam Power Plant

Steam-fraction = 0,2207







- LAMP / GLOBO
- FAN / FAN
- PUMP / POMPA
- MOTOR / MOTOR
- TRANSFORMER
- GENERATOR

LEGENDA		
NO	KODE	Uraian
01	01	TRANSFORMER
02	02	TRANSFORMER
03	03	TRANSFORMER
04	04	TRANSFORMER
05	05	TRANSFORMER
06	06	TRANSFORMER
07	07	TRANSFORMER
08	08	TRANSFORMER
09	09	TRANSFORMER
10	10	TRANSFORMER
11	11	TRANSFORMER
12	12	TRANSFORMER
13	13	TRANSFORMER
14	14	TRANSFORMER
15	15	TRANSFORMER
16	16	TRANSFORMER
17	17	TRANSFORMER

1	REVISI	REVISI
2	REVISI	REVISI
3	REVISI	REVISI
4	REVISI	REVISI
5	REVISI	REVISI

NO	REVISI	REVISI
1	REVISI	REVISI
2	REVISI	REVISI
3	REVISI	REVISI
4	REVISI	REVISI
5	REVISI	REVISI



VTR *veikvirkingslab*
Skóluneyti 1, 101 Reykjavík

VARMATRÖK M.P.
Skóluneyti 1, 101 Reykjavík

NETAVERKA
Skóluneyti 1, 101 Reykjavík

REYKJANESVIRKIUN
VÉLASAMSTÆÐA 1
 HÁSKÓLAHÁSKÓLA
 HÁSKÓLAHÁSKÓLA

Proj. No. **REY C**
 33-MH-1210
 21.01.06



Silbersulfid-Kristalle auf
Chip-Widerstand








HITAVEITA
SUBURNESIA

Reykjanes Power Station






Reykjanes condenser



Inside a
condenser



Gas exhaust system: Steam ejectors and intercondensers



It was difficult to get quality gaskets when asbestos had been banned

91 10 8




Hydrogen sulphide can cause cracks in high manganese steel



HITAVEITA
SUBURNESIA



50 MW turbine, 80 kg/s, 18,0/0,1 bar







Snorkel



Drops from silencers are bad for glass and glossy car surfaces

GRP (Glass Reinforced Plastic) piping must be handled with care



Svartsengi 6 cooling tower. Ice may be a problem.





HITAVEITA
SUBURNEZIA



Remember

- Preserve exergy
- Avoid scaling
- Silica scaling starts at $T_{\text{resevoir}} - 100^{\circ}\text{C}$
- Vertical separators can be over-/underloaded
- Direct contact condenser can cause sulfur scaling in cooling tower and condensers
- Consult operating and maintenance staff

A blurry, low-angle shot of a hallway. The scene is dominated by a bright, overexposed light source at the far end of the hallway, creating a strong lens flare and illuminating the scene. The walls and floor are indistinct due to the blur and low light. The overall color palette is muted, with a mix of greys, browns, and the bright white/yellow of the light source.

Everything clear?